



## RESmart<sup>®</sup> BPAP-20 Series

Bi-level Positive Airway Pressure  
With RESlex<sup>™</sup> (Expiration Pressure Release)



RESmart<sup>®</sup> BPAP-20 Series provide non-invasive ventilation for patients with respiratory insufficiency in the hospital or at home. The breath-by-breath pressure relief of RESlex<sup>™</sup> offers most natural respiratory therapy. It can also offer the ultimate in sleep therapy comfort, with auto adjusting pressure delivery.



### Professional precision

- Monitored parameters include: IPAP, EPAP and Expiration tidal volume (V<sub>te</sub>)
- Quick and easy setting when in use, including: IPAP, EPAP, Res. Rate, E/I Rate, I Sense, E Sense and Rise time
- Innovative tracking technology ensures accurate and comfortable therapy
- Unique sensitivity setting offers individual therapy algorithm, makes every user get the most comfort
- RESlex<sup>™</sup> performs better exhalation and compliance
- Alert when accidental power-off
- In time alert function when mask/tubing off-line
- Automatic leakage and altitude compensation

### Ergonomic and powerful design



- Integrated and knock-down designed InH2<sup>®</sup> heated humidifier
- DC 24V powered and infrared controlled humidifier make user safe and comfortable
- Patented anti-countercurrent water tank
- Unique delay-off feature protects RESmart<sup>®</sup> BPAP from humidity hazard
- Powerful embedded memory stores last night's full raw data and 365 nights' user blog

### Optional accessories

- Heated tubing provides constant temperature and constant relative humidity - Rainout Prevention
- DC to AC convert, makes DC input available to meet the travelling need



## Technical Specifications:

### Device Size

Dimensions: 220 × 194 × 112 mm  
313 × 194 × 112 mm (with InH2<sup>®</sup> heated humidifier)

Weight: < 2.2 kg  
< 3 kg (with InH2<sup>®</sup> heated humidifier)

### Environmental

	Operating	Transport and Storage
Temperature	5 to 30°C	-20 to 55°C
Relative Humidity	≤ 80% Non-condensing	≤ 93% Non-condensing
Atmospheric Pressure	860 to 1060 hPa	500 to 1060 hPa

### Standards Compliance

IEC 60601-1 General Requirements for Safety of Medical Electrical Equipment  
IEC 60601-1-2 Electromagnetic Compatibility  
ISO 17510 Sleep Apnoea Breathing Therapy  
ISO 8185 General Requirements for Humidification Systems

### Electrical

AC Power Consumption: 100 - 240V AC, 50/60Hz, Max 95VA  
Type of Protection Against Electric Shock: Class II Equipment  
Degree of Protection Against Electric Shock: Type BF Applied Part  
Degree of Protection Against Ingress of Water: Drip Proof, IPX1  
Mode of Operation: Continuous

### Model Comparison

Product Model	Pressure	Working Mode	Auto Pressure
RESmart <sup>®</sup> BPAP-20S	4-20 cmH <sub>2</sub> O	CPAP, S	No
RESmart <sup>®</sup> BPAP-20A	4-20 cmH <sub>2</sub> O	CPAP, S, Auto S	Available
RESmart <sup>®</sup> BPAP-20T	4-20 cmH <sub>2</sub> O	CPAP, S, T, S/T	No

## Pressure

IPAP	4 to 20 cmH <sub>2</sub> O	±1 cmH <sub>2</sub> O*
EPAP	4 to 20 cmH <sub>2</sub> O	±1 cmH <sub>2</sub> O*
CPAP	4 to 20 cmH <sub>2</sub> O	±1 cmH <sub>2</sub> O*
Respiratory Rate	3 to 40 BPM	Greater of ±1 BPM or ±10% of the setting (When measured over a 4 minutes period)
E/I Rate	1-6	
Max. Inspiration Time	3.0 seconds	
Ramp Duration	0 to 60 minutes	±10% of the setting
Rise Time	0 to 3**	±25%***
I Sense	1-8	
E Sense	1-8	

\* Dynamic pressure accuracy is ±1 cmH<sub>2</sub>O measured at the patient end of the circuit with a nasal mask and varying flow conditions.

Static pressure accuracy is ±0.5 cmH<sub>2</sub>O measured at the patient end of the circuit with a nasal mask and no patient flow.

\*\* The setting of 0 indicates a Rise Time of 0.1 seconds;  
The setting of 1 indicates a Rise Time of 0.2 seconds;  
The setting of 2 indicates a Rise Time of 0.3 seconds;  
The setting of 3 indicates a Rise Time of 0.4 seconds.

\*\*\* Measured at the patient end of circuit with a flowmeter and no patient flow.

## Disposal

Dispose of the device in accordance with local regulations.

Manufacturer: BMC Medical Co., Ltd.

NOTE: specifications subject to change without prior notice.

V1.0